

Inlet Bags

Inlet Bag Product Specs:

Bag Material Type	Woven Polypropylene Geotextile		
Fabric Property	Test Method	Unit	M.A.R.V.
Grab Tensile	ASTM D-4632	Lbs. (kN)	365 x 200 (1.62 x 0.89)
Grab Elongation	ASTM D-4632	%	15
Trap Tear	ASTM D-4533	Lbs. (kN)	115 x 75 (0.51 x 0.33)
CBR Puncture Resistance	ASTM D-6241	Lbs. (kN)	675 (3.00)
Apparent Opening Size (AOS)*	ASTM D-4751	US Std. Sieve (mm)	40 (0.425)
Permittivity*	ASTM D-4491	Sec ⁻¹	2.1
Water Flow Rate*	ASTM D-4491	gpm/ft ²	230
UV Resistance	ASTM D-4355	%/hrs	90/500
Mullen Burst	ASTM D-3786	psi	450

*At the time of manufacturing. Handling may change these properties.

Item List:

Part Number	Description
FF-IB-2-2-JB	Inlet Bag 2' x 2'
FF-IB-2-3-JB	Inlet Bag 2' x 3'
FF-IB-2-4-JB	Inlet Bag 2' x 4'
FF-IB-4-4-JB	Inlet Bag 4' x 4'