

INSTALLER NETTING



Easy to Install. Hard to Beat.

Filtrex Netting is the original compost filter sock netting for field installation with blower trucks or track machines. Reliable and durable, multiple netting types ensure the right fit for your job.

REVO Installer Netting (5 mil HDPE)

Stable in both the linear and radial orientation, Revo netting doesn't shrink and won't overfill.

BASIC Installer Netting (5 mil HDPE)

Meet all specs with this versatile, light duty netting that is good for most applications.

BASIC+ Installer Netting (MFPP)

Meets or exceeds specs with higher durability. Available in larger diameter sizes, for any project.

Product Name	REVO Installer Netting	Basic Installer Netting	Basic+ Installer Netting
Netting Material Type	5mil High Density Polyethylene (HDPE)	5mil High Density Polyethylene (HDPE)	Multi-Filament Polypropylene (MFPP)
Uses	On-site blower truck installation		
Netting Opening Size	3/8"	3/8"	3/8"
Diameters	12", 18", 24", 32"	12", 18"	8", 12", 18", 24", 32"
Functional Longevity/Project Duration ¹	up to 1 yr	up to 4 yr	up to 4 yr
Tensile Strength (ASTM D4595) ²	52 lbs*	145 lbs	229 lbs
Packaging	Rings	Rucks	Rucks
Netting Color	 blue/black w/ integrated orange staking dot	 orange/black (12")  red/black (18")	 black

¹Functional longevity ranges are estimates only. Site specific environmental conditions may result in significantly shorter or longer time periods. ²Tensile Strength is based on 12" diameter using ATSM D4595, average of MD & TD. See Filtrex TechLink #3342 for full tensile strength testing. *ASTM 5034




REVO NET

CFS Installer Netting

Revo Net Product Specs:

Netting Material Type	REVO Installer Netting 5mil High Density Polyethylene (HDPE)
Netting Degradation	Photodegradable; UV Stability at 1000 Hours: 50%
Netting Diameters	12", 18", 24", 32"
Netting Opening Size	3/8"
Netting Color	Blue/Black with integrated orange dots at 10-ft increments
Fabric Tensile Strength (ASTM 5034)	52 lbs
Functional Longevity ¹	up to 1 year



Netting Sample

¹Functional longevity ranges are estimates only. Site specific environmental conditions may result in significantly shorter or longer time periods.

Item List:

Item Number	Diameter	Unit Type	Length/Unit	Units per box	Units per pallet or Super Sack	Feet per pallet or Super Sack
REVO - 12" Ring	12-in	Ring	125-ft	5 rings	60 rings	7,500-ft
REVO - 18" Ring	18-in	Ring	125-ft	3 rings	36 rings	4,500-ft
REVO - 24" Ring	24-in	Ring	125-ft	2 rings	24 rings	3,000-ft
REVO - 32" Ring	32-in	Ring	125-ft	2 rings	24 rings	3,000-ft


Note: Minimum sales unit is a box. 12 boxes per pallet (Super Sacks have the same ring count as a 12 box pallet)

BASIC NET

CFS Installer Netting

Basic Net Product Specs:

Netting Material Type	BASIC Installer Netting 5mil High Density Polyethylene (HDPE)
Netting Degradation	Photodegradable
Netting Diameters	12", 18"
Netting Opening Size	3/8"
Netting Color	Orange/Black (12"); Red/Black (18")
Fabric Tensile Strength (ASTM D4595) ¹	145 lbs
Functional Longevity ²	up to 4 years



Netting Sample

¹Tensile Strength is based on 12" diameter using ATSM D4595. See Filtrexx TechLink #3342 for full tensile strength testing.
²Functional longevity ranges are estimates only. Site specific environmental conditions may result in significantly shorter or longer time periods.

Item List:

Item Number	Part Reference	Diameter	Unit Type	Length/Unit	Units per pallet	Feet per pallet
Installer - 12" Basic Ruck O-B	430-000253	12-in	Ruck	200-ft	90	18,000-ft
Installer - 18" Basic Ruck R-B	430-000258	18-in	Ruck	200-ft	72	14,400-ft

BASIC+ NET

CFS Installer Netting

Basic+ Net Product Specs:

Netting Material Type	BASIC + Installer Netting Multi-Filament Polypropylene (MFPP)
Netting Degradation	Photodegradable
Netting Diameters	8", 12", 18", 24", 32"
Netting Opening Size	3/8"
Netting Color	Black
Fabric Tensile Strength (ASTM D4595) ¹	229 lbs
Functional Longevity ²	up to 4 years



Netting Sample

¹Tensile Strength is based on 12" diameter using ATSM D4595. See Filtrexx TechLink #3342 for full tensile strength testing.
²Functional longevity ranges are estimates only. Site specific environmental conditions may result in significantly shorter or longer time periods.

Item List:

Item Number	Part Reference	Diameter	Unit Type	Length/Unit	Units per pallet	Feet per pallet
Installer - 8" Basic + Ruck	430-000251	8-in	Ruck	200-ft	112	22,400-ft
Installer - 12" Basic + Ruck	430-000255	12-in	Ruck	200-ft	120	24,000-ft
Installer - 18" Basic + Ruck	430-000260	18-in	Ruck	200-ft	90	18,000-ft
Installer - 24" Basic + Ruck	430-000262	24-in	Ruck	200-ft	70	14,000-ft
Installer - 32" Basic + Ruck	430-000263	32-in	Ruck	200-ft	60	12,000-ft