

STRAW WATTLE

Common Straw Wattle



The flexible BMP option for a variety of sediment & erosion control projects.

Our weed-free Straw Wattles provide perimeter protection along contours or at the base of slopes, inlets, and roadways to reduce soil erosion and runoff, and retain sediment.

Regularly specified on construction sites, "Common" Straw Wattle is comprised of UV-Stabilized extruded netting and weed-free agricultural straw fill. Straw Wattles are an extremely flexible BMP, and easily conform to soil surfaces. Secure wattles by staking and trenching according to site requirements.

MKB Straw Wattles are available in a variety of diameters & lengths for any project.

Applications:

- Perimeters
- Slopes
- Ditches

Benefits:

- Uses traditional UV Stabilized extruded netting
- Lightweight & easy to handle
- Economical & commonly specified
- Efficient quantities per pallet & truckload
- 6", 9", 12", 20" diameters



STRAW WATTLE

Common Straw Wattle

Common Straw Wattle Product Specs:

Netting Material Type	Common Wattle Netting Extruded HDPE High Density Polyethylene Oriented Net
Netting Degradation*	UV Stabilized Photodegradable - 12 months
Netting Diameters	6", 9", 12", 18/20"
Netting Opening Size/Shape	3/8" / Diamond
Netting Color	Black
Fabric Tensile Strength (Test Method RW82004)	52.8 lbs
Fill Type	Weed/Seed Free Agricultural Straw
Staking Recommendation	Every 5-ft (stakes not included)
Applications	Sediment Removal, Slope Interruption



Netting Sample



Fill Sample

Note: take care when adjusting product after installation.

*Degradation and longevity ranges are estimates only. Site specific environmental conditions may result in significantly shorter or longer time periods.

Item List:

Item Number (Black Net)	Diameter	Total Linear Feet per pallet	Unit Length	Units per pallet*	Unit Weight	Pallet Weight
SW6-30-15	6-in	450-ft	15-ft	30		
SW6-16-30	6-in	480-ft	30-ft	16		
SW9-12-25	9-in	300-ft	25-ft	12	33 lb +/- 10%	~ 455 lbs
SW9-14-25	9-in	350-ft	25-ft	14	33 lb +/- 10%	~ 520 lbs
SW9-24-10	9-in	240-ft	10-ft	24	16 lb +/- 10%	~ 445 lbs
SW12-20-10	12-in	200-ft	10-ft	20	25 lb +/- 10%	~ 560 lbs
SW12-10-20	12-in	200-ft	20-ft	10	50 lb +/- 10%	~ 560 lbs
SW20-14-10	20-in	140-ft	10-ft	14	22 lb +/- 10%	~ 350 lbs
SW20-7-20	20-in	140-ft	20-ft	7	43 lb +/- 10%	~ 350 lbs

*Units per pallet may vary by regional manufacturing facility & availability.

Shipping Specs:

Pallets per TL	up to 28
Shipping Dimensions	up to 48L x 48W x 108H (height varies by product type)
Packaging	48 x 48 Pallet; Wattles are strapped together, and pallet is stretch-wrapped
Storage Life	Under Roof - 6 months / Outdoors - 3 months