

ROADWATTLE®

Portable Filter Sock



Sometimes you need a filter sock that can be moved.

RoadWattle is the answer – it's designed for daily portability. Use it across access roads at night, during rainouts, and near stream crossings on pipeline and powerline projects.

RoadWattle is filled with chopped switchgrass – a PADEP - approved alternative fill material for Compost Filter Sock.

RoadWattle weighs 50% less than Compost Filter Sock and is made of heavy duty textile and strapping – enabling the device to be moved again and again.

Comes in Hi-Vis orange for maximum visibility.

Benefits:

- Available in 12 and 18 foot lengths
- Textile is 1/8-inch opening heavy-duty Polyethylene
- Four integrated straps for easy moving
- Fill is chopped switchgrass or pine straw
- Sock quickly dries and is moveable after rain event
- Available coiled on a pallet or in a super sack
- Field longevity of up to one year
- Approved by PA DEP for HQ and EV watersheds
- Can be staked through or driven over (if necessary)
- Available in Hi-Vis orange for maximum visibility



MKB Stormwater
Innovation

888-578-0777
mkbcompany.com

©2024 MKB Company. All Rights Reserved.

Made in U.S.A.


All statements, product characteristics, and performance data contained herein are believed to be reliable based on observation and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the results to be obtained. Nothing contained herein is to be considered to be permission or a recommendation to use any proprietary process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended. Filtrixx® and the branch & leaf logo® are Registered Trademarks of MKB Company. US Patents and Patents Pending may apply.

ROADWATTLE®

Portable Filter Sock

RoadWattle Product Specs:

Netting Material Type	275g/m ² reinforced slit film Polyethylene
Netting Color	Blaze Orange
Netting Diameters	9.5", 12"
End Closure	hog rings -or- zip ties
Handling Straps	4 per unit (blue)
Fabric Tensile Strength (ASTM D 4632)	MD – 267 lbs. TD – 168 lbs.
Elongation at Max Load (ASTM 4632)	MD – 66% TD – 109%
Permittivity g/m/ft ² (ASTM D 4491 C)	180 g/m/ft ²
Fill Type	Switchgrass
Functional Longevity ¹	Up to 1 year



Netting Sample



Fill Sample

¹Functional longevity ranges are estimates only. Site specific environmental conditions may result in significantly shorter or longer time periods.

Item List:

Item Number	Diameter	Total Linear Feet per pallet	Unit Length	Units per pallet	Unit Weight	Pallet Weight
RW95-12-SG	9.5-in	240-ft	12-ft	20	~ 41 lbs	~ 875 lbs
RW95-18-SG	9.5-in	252-ft	18-ft	14	~ 60 lbs	~ 895 lbs
RW12-10-SG	12-in	100-ft	10-ft	10	~ 60 lbs	~ 655 lbs

Shipping Specs:

Pallets per TL	up to 28
Shipping Dimensions	40L x 48W x 66H
Packaging	40 x 48 Pallet; Wattles are strapped together, and pallet is stretch-wrapped
Storage Life	Under Roof - 6 months / Outdoors - 3 months