

ROCKSOXX™

Stormwater Filter



Trap sediment from stormwater runoff that flows onto roadways from construction activities.

Weighted, durable, and reusable, RockSock stays put in concentrated flows without trenching, stakes, or anchors. High-strength netting and double hog rings allows for RockSock to be repeatedly run over and moved – and still last the entire job.

Applications include:

- Ditch checks
- Inlet protection
- Gutter-line checks
- Perimeter sediment control repairs

Benefits:

- Modular pieces allow for flexible configurations
- High hydraulic flow to prevent ponding
- Heavy enough to stay in place without anchors
- Netting is a high-flow, high-strength, UV-resistant multi-filament polyester knit textile
- Color is Hi-Vis Safety Orange
- Fill is a 50-50 blend of 1½" (minus) dust-free limestone gravel and composted hardwood chip
- 6-inch pig tails for easy handling
- Double hog ring closure prevents opening

double
pig tails

double
hog rings


36



RockSoxx Product Specs:

Netting Material Type	HV-X Heavy Duty Multi-Filament Polyester UV Resistant
Netting Color	Hi-Vis Orange
Netting Diameters	8"
Netting Opening Size	1/8"
End Closure	6-inch pig tails with double hog ring closure
Fabric Tensile Strength (ASTM 5035)	497 psi
Fill Type	50% 1 ½"(minus) dust-free limestone gravel 50% composted hardwood chip
Functional Longevity ¹	up to 3 years

¹Functional longevity ranges are estimates only. Site specific environmental conditions may result in significantly shorter or longer time periods.



Netting Sample



Gravel Fill Sample



Hardwood Chip
Fill Sample

Item List:

Item Number	Diameter	Total Linear Feet per pallet	Unit Length	Units per pallet	Unit Weight	Pallet Weight
RS-8-36	8-in	120-ft	3-ft	40	50 lbs	2000 lbs

Shipping Specs:

Pallets per TL	up to 20
Shipping Dimensions	40L x 48W x 66H
Packaging	40 x 48 Pallet with Plastic Stretch-Wrap
Storage Life	Under Roof - 6 months / Outdoors - 3 months