

STORMCATCHER®

Weighted Sediment Filter Tube



Robust, flexible BMP for people and places where performance matters.

StormCatcher is a multipurpose tubular BMP, used where a temporary robust filter berm is needed. The textile is tough and long-lasting.

Filled with a patent-pending heat-treated rice hull mixed with gravel that forms a high flow, high sediment retention 3-dimensional filtering matrix.

Similar products that use old ground up tires just can't do this. Plus, the the biodegradable rice hull media can be left on site, forming a soil amendment – rubber can't.

Benefits:

- Textile is 1/8-inch opening heavy-duty Polyethylene
- Four integrated straps for easy moving
- Fill is all-natural rice hulls and gravel
- No sharp wires
- Lighter and easier to handle than rubber-filled wattles
- Field longevity of up to one year
- Available in Hi-Vis orange for maximum visibility



MKB Stormwater
Innovation

888-578-0777
mkbcompany.com

©2025 MKB Company. All Rights Reserved.

Made in U.S.A.


All statements, product characteristics, and performance data contained herein are believed to be reliable based on observation and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the results to be obtained. Nothing contained herein is to be considered to be permission or a recommendation to use any proprietary process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended. Filtrrex®, Storm Catcher®, and the branch & leaf logo® are Registered Trademarks of MKB Company. US Patents Pending 63/070,891 may apply.

STORMCATCHER®

Weighted Sediment Filter Tube

StormCatcher Product Specs:

Netting Material Type	275g/m ² reinforced slit film PE
Netting Color	Blaze Orange
End Closure	hog rings -or- zip ties
Handling Straps	4 per unit (blue)
Fabric Tensile Strength (ASTM D 4632)	MD – 267 lbs. TD – 168 lbs.
Elongation at Max Load (ASTM 4632)	MD – 66% TD – 109%
Permittivity g/m/ft ² (ASTM D 4491 C)	180 g/m/ft ²
Fill Type	Heat-Treated Rice Hulls 50% Gravel fill on 9-inch only
Functional Longevity ¹	Up to 1 year



Netting Sample



Rice Hull Fill Sample



Gravel Fill Sample

¹Functional longevity ranges are estimates only. Site specific environmental conditions may result in significantly shorter or longer time periods.

Item List:

Item Number	Diameter	Total Linear Feet per pallet	Unit Length	Units per pallet	Unit Weight	Pallet Weight
WST9-4	9-in	192-ft	4-ft	48	~ 33 lbs	~ 1560 lbs
WST9-8	9-in	192-ft	8-ft	24	~ 65 lbs	~ 1560 lbs
WST9-10	9-in	220-ft	10-ft	22	~ 81 lbs	~ 1782 lbs
WST9-12	9-in	240-ft	12-ft	20	~ 98 lbs	~ 1960 lbs
WST12-10	12-in	100-ft	10-ft	10	~ 115 lbs	~ 1150 lbs

Shipping Specs:

Pallets per TL	up to 20
Shipping Dimensions	40L x 48W x 66H
Packaging	Super Sack
Storage Life	Under Roof - 6 months / Outdoors - 3 months