

ROCK LOG

Stormwater Filter



Versatile, weighted BMP that helps minimize runoff on hard surfaces or landscape areas.

Rock Logs are a popular construction site BMP, designed to filter sediment and slow water velocity. This weighted BMP is easy to install on any earth or hard surface and does not require trenching, staking, or anchors. The high-strength, UV-resistant netting ensures that Rock Logs can be moved around while their modular design allows for flexible configurations – simply overlap unit edges as needed.

Use Rock Logs for common sediment control applications including:

- Ditch checks
- Inlet protection
- Perimeter control

Benefits:

- Durable, UV-resistant netting
- Reusable and modular
- Heavy enough to stay in place without anchors or stakes
- Use on hard surfaces
- Available in 4-ft or 6-ft lengths



888-578-0777
mkbcompany.com

©2026 MKB Company. All Rights Reserved.

Made in U.S.A.

All statements, product characteristics, and performance data contained herein are believed to be reliable based on observation and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the results to be obtained. Nothing contained herein is to be considered to be permission or a recommendation to use any proprietary process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended.

ROCK LOG

Stormwater Filter

Rock Log Product Specs:

Fabric Material Type	High Density Polyethylene (HDPE) UV Resistant
Fabric Color	Black
Fabric Diameter	6"
Fabric Apparent Opening	Equivalent Sieve Size: 12
Fabric Breaking Strength Grab Method lbs (ASTM D-4632)	Warp: 137 lbs Fill: 79 lbs
Fabric Breaking Elongation Grab Method % (ASTM D-4632)	Warp: 75.6% Fill: 64.8%
Fabric Puncture Resistance (ASTM D-4833)	66 lbs
Fabric UV Resistance (500 hrs) (ASTM D-4355)	> 70%
Fill Type	Washed 3/4" rock



Netting Sample



Rock Fill Sample

Meets/exceeds spec for WI DOT 628.2.13 Rock Bags.

Item List:

Item Number	Diameter	Total Linear Feet per pallet	Unit Length	Units per pallet	Unit Weight	Pallet Weight
RL-25-4	6-in	100-ft	4-ft	25	~ 61 lbs	~ 1526 lbs
RL-25-6	6-in	150-ft	6-ft	25	~ 97 lbs	~ 2427 lbs

Shipping Specs:

Pallets per TL	up to 20
Shipping Dimensions	49L x 49W x 62H
Packaging	48 x 48 Pallet with Plastic Stretch-Wrap
Storage Life	Under Roof - 6 months / Outdoors - 3 months